

Guided Type Fall Arrester

Model No.	78 RORIP 78R-8
Applicable Rope Size	16mm
Dimension (L × W)	113 × 52mm
Material	Steel
Weight	720g
Plating	Zincd
Breaking Strength	16kN (Nylon Rope)
Slippage	10 – 170 mm (Nylon Rope)
Remark For ascending & descending work and work at fixed position.	






Model No.	78 RORIP 78R-15-8
Applicable Rope Size	16mm
Dimension (L × W)	113 × 52mm
Material	Steel
Weight	720g
Plating	Zincd
Breaking Strength	16kN (Nylon Rope)
Slippage	10 – 170 mm (Nylon Rope)
Remark For ascending & descending work and work at fixed position.	



Model No.	SS RORIP SS21
Applicable Rope Size	16~18mm
Dimension (L × W)	108 × 52mm
Material	Steel
Weight	500g
Plating	Chromed
Breaking Strength	13.8kN (Nylon Rope)
Slippage	
Remark For ascending & descending work.	



Ring & Buckle

Model No.	FL-03-6	
Applicable Belt Size	45mm	
Dimension (L × W)	54 × 51.5 × 180° φ 7.0mm	
Type	D-Ring	
Material	Steel	
Weight	85g	
Surface Treatment	Zincd or Chromed	
Breaking Strength	32.3kN	
Remark		
Model No.	FL-03-8	
Applicable Belt Size	45mm	
Dimension (L × W)	54 × 47 × 130° φ 7.0mm	
Type	D-Ring	
Material	Steel	
Weight	85g	
Surface Treatment	Zincd or Chromed	
Breaking Strength	32.3kN	
Remark		
Model No.	FL-10	
Applicable Rope Size	φ 16mm	
Dimension (L × W)	20 × 20 × 180° φ 6.0mm	
Type	8-Ring	
Material	Steel	
Weight	40g	
Surface Treatment	Zincd or Chromed	
Breaking Strength	25.5kN	
Remark		

Model No.	FL-88	
Applicable Rope Size	ϕ 16mm	
Dimension (L × W)	20 × 24 × 180° t6.35mm	
Type	8-Ring	
Material	Steel	
Weight	60g	
Surface Treatment	Zincd or Chromed	
Breaking Strength	29.4kN	
Remark		
Model No.	FB-Y45PU	
Available Belt Width	45mm	
Type	Slide Buckle	
Dimension (L × W)	80 × 73 mm	
Material	Steel	
Weight	130g	
Surface Treatment	Zincd or Chromed	
Remark		

Snap Hook

Model No.	FS-33
Overall Length	70mm
Effective Opening	9.5mm
Eye Diameter	16mm
Material	Steel
Weight	115g
Surface Treatment	Chromed
Breaking Strength	20.6kN
Remark	Pressed



Model No.	FS-33KS
Overall Length	105mm
Effective Opening	9.5mm
Eye Diameter	NS8mm
Material	Steel
Weight	205g
Surface Treatment	Chromed
Breaking Strength	17.4kN
Remark	Swivel Hook Pressed



Model No.	FS-50
Overall Length	115mm
Effective Opening	13mm
Eye Diameter	16mm
Material	Steel
Weight	230g
Surface Treatment	Nickeled or Zined
Breaking Strength	20.1kN
Remark	Pressed



Model No.	FS-51L
Overall Length	128mm
Effective Opening	18mm
Eye Diameter	23mm
Material	Steel
Weight	250g
Surface Treatment	Nickel or Zinc
Breaking Strength	23.5kN
Remark	Pressed



Model No.	FS-55
Overall Length	117mm
Effective Opening	13mm
Eye Diameter	16mm
Material	Aluminum
Weight	140g
Surface Treatment	See Below *
Breaking Strength	18.4kN
Remark	Drop Forged * Safety catch and Lock catch: chromed



Model No.	FS-57L
Overall Length	176mm
Effective Opening	18mm
Eye Diameter	21mm
Material	Aluminum
Weight	260g
Surface Treatment	See Below *
Breaking Strength	15kN
Remark	Drop Forged Swivel Hook * Safety catch and Lock catch: chromed



Model No.	FS-60
Overall Length	132mm
Effective Opening	13mm
Eye Diameter	23mm
Material	Steel
Weight	250g
Surface Treatment	Chromed
Breaking Strength	23.4kN
Remark	Pressed



Model No.	FS-61
Overall Length	181mm
Effective Opening	24mm
Eye Diameter	23mm
Material	Steel
Weight	458g
Surface Treatment	Zincd
Breaking Strength	22.7kN
Remark	Pressed



Model No.	FS-62-2
Overall Length	147mm
Effective Opening	9mm
Eye Diameter	6.5 × 46mm
Material	Steel
Weight	300g
Surface Treatment	Zincd
Breaking Strength	23.5kN
Remark	Pressed Belt Slot Type



Model No.	FS-70
Overall Length	157mm
Effective Opening	13mm
Eye Diameter	21mm
Material	Steel
Weight	325g
Surface Treatment	Chromed or Zinced
Breaking Strength	20kN
Remark Drop Forged Swivel Hook	



Model No.	FS-76
Overall Length	190mm
Effective Opening	13mm
Eye Diameter	21mm
Material	Steel
Weight	415g
Surface Treatment	Chromed
Breaking Strength	20kN
Remark Drop Forged Swivel Hook	



Model No.	FS-90
Overall Length	216mm
Effective Opening	50mm
Eye Diameter	20mm
Material	Steel
Weight	410g
Surface Treatment	Nickeled
Breaking Strength	22.5kN
Remark Drop Forged	



Model No.	FS-92
Overall Length	330mm
Effective Opening	85mm
Eye Diameter	25mm
Material	Steel
Weight	830g
Surface Treatment	Nickeled
Breaking Strength	22kN
Remark Round Bar Type	




Model No.	FS-93
Overall Length	216mm
Effective Opening	50mm
Eye Diameter	20mm
Material	Steel
Weight	265g
Surface Treatment	Nickeled
Breaking Strength	14.7kN
Remark Pressed Light weight model	



Model No.	FS-99
Overall Length	216mm
Effective Opening	50mm
Eye Diameter	20mm
Material	Steel
Weight	350g
Surface Treatment	Nickeled
Breaking Strength	15.5kN
Remark Drop Forged	



Model No.	FS-100L
Overall Length	163mm
Effective Opening	16.5mm
Eye Diameter	21mm
Material	Steel
Weight	240g
Surface Treatment	Chromed
Breaking Strength	19.6kN
Remark Drop Forged Swivel Hook	



Model No.	FS-101-2
Overall Length	185mm
Effective Opening	19mm
Eye Diameter	21mm
Material	Steel
Weight	230g
Surface Treatment	Chromed
Breaking Strength	19.6kN
Remark Drop Forged Swivel Hook	



Model No.	FS-110
Overall Length	185mm
Effective Opening	19mm
Eye Diameter	21mm
Material	Steel
Weight	350g
Surface Treatment	Chromed
Breaking Strength	23.0kN
Remark Drop Forged Swivel Hook	



Model No.	FS-108	
Overall Length	184mm	
Effective Opening	14mm	
Eye Diameter	21mm	
Material	Steel	
Weight	325g	
Surface Treatment	Nickeled	
Breaking Strength	19.6kN	
Remark Drop Forged Swivel Hook Triple Locking		

Rope Adjuster (Adjusting Implement)

Model No.	FC-100
Applicable Rope Size	16mm
Dimension (L × W)	82 × 77 × 68
Material	Steel
Weight	400g
Surface Treatment	Chromed
Breaking Strength	11.8kN
Remark FC Effective opening of Connecting Hook : 7.5mm For U-shaped suspension only	



Model No.	12D-7/I
Applicable Rope Size	12mm
Dimension (L × W)	83 × 60 × 68
Material	Steel
Weight	410g
Surface Treatment	Zincd
Breaking Strength	14.2kN
Remark 12D Effective opening of Connecting Hook : 7.5mm For both U-shaped and single-line suspension	



Model No.	12D-7/DH
Applicable Rope Size	12mm
Dimension (L × W)	83 × 60 × 90
Material	Steel
Weight	460g
Surface Treatment	Zincd
Breaking Strength	14.2kN
Remark Effective opening of Connecting Hook : 12mm For both U-shaped and single-line suspension	



Model No.	12D-7/R
Applicable Rope Size	12mm
Dimension (L × W)	83 × 60 × 63.5
Material	Steel
Weight	350g
Surface Treatment	Zincd
Breaking Strength	14.2kN
Remark Connecting Ring dia.: 20mm For both U-shaped and single-line suspension	



Model No.	T-537/DH
Applicable Rope Size	16mm
Dimension (L × W)	98 × 77 × 90
Material	Steel
Weight	590g
Surface Treatment	Chromed
Breaking Strength	19.1kN
Remark Effective opening of Connecting Hook : 12mm For both U-shaped and single-line suspension	



Model No.	T-537/I
Applicable Rope Size	16mm
Dimension (L × W)	98 × 77 × 63.5
Material	Steel
Weight	500g
Surface Treatment	Chromed
Breaking Strength	19.1kN
Remark 63D Effective opening of Connecting Hook : 7.5mm For both U-shaped and single-line suspension	



Model No.	T-537/R
Applicable Rope Size	16mm
Dimension (L × W)	98 × 77 × 63.5
Material	Steel
Weight	460g
Surface Treatment	Chromed
Breaking Strength	19.1kN
Remark Connecting Ring dia.: 20mm For both U-shaped and single-line suspension	



Model No.	16D-100
Applicable Rope Size	16mm
Dimension (L × W)	100 × 75 × 81
Material	Aluminum
Weight	310g
Surface Treatment	—
Breaking Strength	17.6kN
Remark 16D, TD Effective opening of Connecting Hook : 7.5mm For both U-shaped and single-line suspension	



Rope Tension Device

Model No.	54 HARIP 54HR	
Available Rope	16mm dia. Nylon rope	
Use for	Horizontal Lifeline	
Tightening strength	2.0kN	
Tensile strength	17.4kN	
Dimension	215 × 95 × 72mm	
Weight	1.7kg	
Remark Maximum Lifeline Span – 15m		
Model No.	Guide Lock GR-1	
Available Rope	16mm dia. Nylon rope	
Use for	Vertical Lifeline	
Tightening strength	2.0kN	
Tensile strength	17.2kN	
Dimension	215 × 95 × 72mm	
Weight	1.7kg	
Remark		